Axial Fans

- All AC units are rated at 50/60 Hz. (50 Hz. operation will decrease CFM by 20%)
- Sleeve bearing fans must be mounted for horizontal airflow only
- Single speed
- Includes 12" wire leads unless noted (*terminal connections)







ALUMINUM HOUSING WITH TERMINALS

ALUMINUM HOUSING WITH LEADS

PLASTIC HOUSING WITH LEADS

Item Number	CFM	Volts	Watts	Amps	Dimension In " (mm)	Mounting Holes OC " (mm)	Price		
PBT Plastic Housing									
Driven with brushless DC motor									
4WT35	36.5	12DC	1.4	.12	3.13(79.5) x 3.13(79.5) x 1.00(25.4)	2.81(71.3)	\$43.72		
6KD70	138	12DC	10.0	.833	4.69(119.1) x 4.69(119.1) 1.50(38.1)	4.13(104.9)	\$71.92		
6KD74	138	24DC	9.2	.383	4.69(119.1) x 4.69(119.1) 1.50(38.1)	4.13(104.9)	\$76.30		
Cast-Aluminum Housing									
Driven with impedance-protected shaded pole or thermally protected PSC motor									
4WT40	30	115 AC	12	0.13	3.13(79.5) x 3.13(79.5) x 1.5(38.1)	2.81(71.3)	\$62.40		
4WT41	30	230 AC	16	0.08	3.13(79.5) x 3.13(79.5) x 1.5(38.1)	2.81(71.3)	\$57.58		
4WT48*	70	115 AC	11	0.13	4.69(119.1) x 4.69(119.1) 1.50(38.1)	4.13(104.9)	\$58.02		
4WT47*	105	115 AC	18	0.18	4.69(119.1) x 4.69(119.1) 1.50(38.1)	4.13(104.9)	\$47.80		
4WT33*	105	230 AC	19	0.11	4.69(119.1) x 4.69(119.1) 1.50(38.1)	4.13(104.9)	\$60.24		

Fan Accessories

- Wire guards are nickel chrome plated and can withstand 220 lb. separation force
- Plastic guards are made of UL listed 94V-0 material
- Plastic assemblies contain: fan guard, foam filter media, and retainer
- Cord sets are type SPT-1, 18/2 AWG, plugs into terminals of all standard 115 or 230 volts axial fans



GUARDS & CORDS

Item Number	Description	Dimension in " (mm)	Price
4YD95	Plastic Guard Assembly	3.13(79.5)	\$6.70
31CC66	Plastic Guard Assembly	4.71(119.6)	\$7.52
4YD96	Wire Guard (115/230V)	3.13(79.5)	\$7.24
4YD87	Wire Guard	4.71(119.6)	\$4.70
4YD79	Cord Set for Axial Fan	24L / 90° Head	\$3.90